


## 5060


### **S** Llave combinada en pulgadas

ANSI/ASME B107.6



- en pulgadas
- Ojo inclinado a 15°
- Cabeza de estrella bi-hexagonal
- Grosor reducido
- Acabado Cromado Pulido



	Dimensión (Inch)	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	L (mm)	Peso (g)
506008	1/4"	15.5	10.1	3.9	4.7	105	18
506010	5/16"	19.2	12.8	4.3	5.5	125	25
506012	3/8"	23.2	15.6	4.7	6.5	145	39
506014	7/16"	25.3	16.9	5.1	6.9	155	46
506016	1/2"	29.4	19.7	5.6	7.8	175	69
506018	9/16"	31.5	21.2	5.9	8.3	185	80
506020	5/8"	34.7	24	6.4	8.9	205	111
506022	11/16"	36.5	25.3	6.6	9.3	215	119
506024	3/4"	40.7	28.1	7.1	10.5	235	158
506026	13/16"	44.8	31.3	7.7	11.3	255	203
506028	7/8"	46.9	32.6	7.9	11.5	265	220
506030	15/16"	50.4	35.5	8.4	12.1	285	287
506032	1"	52	36.9	8.6	12.5	295	326



**KING TONY**

*Enjoy your work*

506034	1-1/16"	55.7	39.6	9.1	13.1	315	371
506036	1-1/8"	59.7	42.3	9.6	13.5	335	456
506040	1-1/4"	65.8	46.4	10.1	14.3	365	557