


904



Bague

- Sécurité pour les serrages pneumatiques
- Bague en caoutchouc

	Longueur (mm)	ø D (mm)	Pour application des séries	Poids (g)
90401	19	3,5	4535M (8~14mm) 4435M (8~14mm) 4015M (5~14mm) 4055M (4~14mm) 4935M (10~14mm) 4415M (17mm) 4835M (10~17mm) 4530M (8~14mm) 4535S (15/16"~9/16") 4435S (15/16"~9/16") 4015S (1/4"~1/2") 4055S (3/16"~1/2") 4935S (7/16"~9/16") 4575 (E10~E18)	2
90402	23	3,5	4535M (15~46mm) 4435M (15~46mm) 4015M (17.19mm) 4415M (19.21mm) 4530M (15~36mm) 4575M (E20) 4835M (19~30mm) 4535S (11/16"~1-1/4") 4435S (5/8"~1-1/4") 4935M (16~30mm) 4935S (11/16"~1-1/4") 4260, 4796, 4797, 4863, 4873, 4866	2
90403	33	3,5	6015M (14~19mm) 6510M (17~30mm) 6515M (17~30mm) 6435S (3/4"~1") 6535S (2



KING TONY

Enjoy your work

			11/16"~1-3/16") 6935S (3/4"~1") 609616M, 609622M	
90404	37	5,5	6535M (17~46mm) 6435M (19~46mm) 6935M (19~32mm) 6015M (21~27mm) 6530M (17~46mm) 6835M (17~32mm) 6535S (1-1/4" ~ 1-13/16") 6435S (1-1/16"~1-13/16") 6935S (1-1/16"~1-1/4") 609622M	2
90405	44	5,5	6535M (48~65mm) 6435M (48~50mm) 6535S (1-7/8" ~ 2-3/8") 6435S (1-7/8" ~ 2")	2
90406	75	10	8535M (71~90mm) 8535S (2-13/16"~3-1/2")	4