


906

Goupille

DIN 3129

- Sécurité pour les serrages pneumatiques
- Chrome Vanadium



	Longueur (mm)	ø D (mm)	Pour application des séries	Poids (g)
90608	14	2,5	3535M (6~12mm) 3435M (6~12mm) 3055M (4~12mm) 3065M (4~12mm) 3575M (E5~E14) 3535S (1/4"~1/2") 3435S (1/4"~1/2") 3055S (3/16"~1/2") 3053 (T10~T50) 3147, 3862, 3864	1
90609	16	2,5	3535M (13~19mm) 3435M (13~24mm) 3535S (9/16"~3/4") 3435S (9/16"~7/8") 3260, 3796	1
90601	20	3	4535M (8~14mm) 4435M (8~14mm) 4015M (5~14mm) 4055M (4~14mm) 4935M (10~14mm) 4415M (17mm) 4835M (10~17mm) 4530M (8~14mm) 4535S (15/16"~9/16") 4435S (15/16"~9/16") 4015S (1/4"~1/2") 4055S (3/16"~1/2") 4935S (7/16"~9/16") 4575 (E10~E18)	2
90602	25	3	4535M (15~46mm) 4435M (15~46mm)	2



KING TONY

Enjoy your work

			4015M (17.19mm) 4415M (19.21mm) 4530M (15~36mm) 4575M (E20) 4835M (19~30mm) 4535S (11/16"~1-1/4") 4435S (5/8"~1-1/4") 4935M (16~30mm) 4935S (11/16"~1-1/4") 4260, 4796, 4797, 4863, 4873, 4866	
90603	35	4	6535M (17~46mm) 6435M (19~46mm) 6935M (19~32mm) 6015M (21~27mm) 6530M (17~46mm) 6835M (17~32mm) 6535S (1-1/4" ~ 1-13/16") 6435S (1-1/16"~1-13/16") 6935S (1-1/16"~1-1/4") 609622M	2
90604	45	4	6535M (48~65mm) 6435M (48~50mm) 6535S (1-7/8" ~ 2-3/8") 6435S (1-7/8" ~ 2")	2
90605	45	5	8535M (19~70mm) 8435M (24~60mm) 8835M (24~60mm) 8535S (3/4"~2-3/4") 8435S (15/16"~2-1/4") 8514M, 8514S, 8534M, 806519M	3
90606	75	5	8535M (71~90mm) 8535S (2-13/16"~3-1/2")	4