

1432


Tournevis de précision à fente

DIN 5263



- Lame ronde
- Lame en SNCM+V, empreinte traitée
- Poignée en PP (polypropylène)
- Section rotative en bout de tournevis
- Finition chromée polie



	Largeur de l'empreinte (mm)	Épaisseur de l'empreinte (mm)	Longueur de la lame (mm)	ø (mm)	Poids (g)
14320615	0.6	0.15	40	3.0	9
14320815	0.8	0.19	40	3.0	9
14321015	1.0	0.20	40	3.0	10
14321515	1.5	0.23	40	3.0	9
14321815	1.8	0.30	40	3.0	9
14322015	2.0	0.40	40	2.0	7
14322515	2.5	0.40	40	2.5	11
14323015	3.0	0.50	40	3.0	13
14323515	3.5	0.60	40	3.5	14
14324015	4.0	0.80	40	4.0	15
14321003	1.0	0.20	75	3.0	12
14321503	1.5	0.23	75	3.0	11
14321803	1.8	0.30	75	3.0	12

14322003	2.0	0.40	75	2.0	13
14322503	2.5	0.40	75	2.5	13
14323003	3.0	0.50	75	3.0	14
14323503	3.5	0.60	75	3.5	17
14324003	4.0	0.80	75	4.0	19