



34_62_DG


Heavy duty adjustable torque wrench

DIN ISO 6789 & ASME B107.300-2010



- ±3% torque accuracy (clockwise)
- Clockwise (CW) and counter-clockwise (CCW) triggering
- 2 way ratchet head
- Quick release button (except 3/4" and 1")
- Easy-to-read scale
- Designed for an easy torque adjustment.
- Set torque using the KING TONY band
- Delivered with calibration certificate
- Reversal of rotation direction by lever
- Non swapable head
- Single scale: Newton Meter (Nm)
- Comfortable rubber handle
- Wide range of choice distinct laser scale.
- Quick automatic return adjustment.



	Square drive	Gear (teeth)	Torque Range (Nm)	Increase (Nm)	L (mm)	Weight (g)
342621DG	1/4"	24	4~20	0.1	324	640
342622DG	1/4"	24	2~10	0.1	281	560
342623DG	1/4"	24	5~30	0.5	325	640
343621DG	3/8"	32	4~20	0.1	324	640
343622DG	3/8"	32	20~100	0.5	435	1300
343623DG	3/8"	32	10~60	0.5	325	1300
344621DG	1/2"	32	40~200	1	521	1590



KING TONY

Enjoy your work

344622DG	1/2"	32	60~340	2	613	1810
344623DG	1/2"	32	20~100	1	435	1300
344624DG	1/2"	32	80~400	2	613	1970
346621DG	3/4"	24	100~600	5	1048	5600
346622DG	3/4"	24	150~800	5	1234	5600
346623DG	3/4"	24	200~1000	5	1238	6150
348621DG	1"	24	200~1000	5	1238	6150