


## 345\_DG


### Heavy duty interchangeable torque wrench

DIN ISO 6789 & ASME B107.300-2010



- Delivered without bits
- $\pm 3\%$  torque accuracy (clockwise)
- Clockwise (CW) and counter-clockwise (CCW) triggering
- Easy-to-read scale
- Set torque using the KING TONY band
- Comfortable rubber handle
- Compatible with standard insert tools
- Wide range of choice distinct laser scale.
- Single scale: Newton Meter (Nm)
- Quick automatic return adjustment.
- Delivered with calibration certificate



	End fitting	Torque Range (Nm)	Increase (Nm)	L (mm)	Weight (g)
345121DG	9x12	2~10	0.1	261	510
345122DG	9x12	4~20	0.1	306	590
345123DG	9x12	20~100	0.5	430	1270
345124DG	9x12	10~60	0.5	306	590
345221DG	14x18	20~100	0.5	430	1270
345222DG	14x18	40~200	1	485	1410
345223DG	14x18	60~340	2	580	1590



**KING TONY**

*Enjoy your work*

345224DG	14x18	100~600	5	1015	6200
345225DG	14x18	10~60	0.5	360	1270
345226DG	14x18	150~800	5	1195	6620
345227DG	14x18	70-350	2	580	1800
345228DG	14x18	200-1000	5	1200	6620
345229DG	14x18	80-400	2	580	1780