



4535S

S 1/2" standard imperial 6 points impact socket

ANSI / ASME B107.2

- Inch
- Chrome molybdenum
- Phosphate finish



|  | Dimension (Inch) | D1 (mm) | D2 (mm) | L (mm) | l (mm) | Weight (g) |
|--|------------------|---------|---------|--------|--------|------------|
| 453510S | 5/16" | 14 | 25 | 38 | 7 | 67 |
| 453512S | 3/8" | 17 | 25 | 38 | 7 | 70 |
| 453514S | 7/16" | 18 | 25 | 38 | 8 | 71 |
| 453516S | 1/2" | 20 | 25 | 38 | 10 | 72 |
| 453518S | 9/16" | 22 | 25 | 38 | 10 | 77 |
| 453520S | 5/8" | 24 | 25 | 38 | 11 | 112 |
| 453522S | 11/16" | 26 | 30 | 38 | 12 | 115 |
| 453524S | 3/4" | 28 | 30 | 38 | 13 | 120 |
| 453526S | 13/16" | 30 | 30 | 40 | 14 | 125 |
| 453528S | 7/8" | 32 | 30 | 40 | 14 | 143 |
| 453530S | 15/16" | 34 | 30 | 42 | 15 | 152 |
| 453532S | 1" | 36 | 30 | 42 | 15 | 168 |
| 453534S | 1-1/16" | 38 | 30 | 44 | 16 | 176 |



KING TONY

Enjoy your work

| | | | | | | |
|---------|---------|----|----|----|----|-----|
| 453536S | 1-1/8" | 41 | 30 | 44 | 17 | 194 |
| 453538S | 1-3/16" | 42 | 30 | 44 | 17 | 201 |
| 453540S | 1-1/4" | 44 | 30 | 44 | 18 | 205 |