

9DM2352



AC/DC Clamp Meter

Approval: CE IEC 61010-1 , IEC 61010-2-032
CAT.III 600V Pollution level 2

- Maximum clamp size: Ø 30mm
- Unit and function indication, maximum value displayed 1999
- Negative polarity indicator (no indicator for positive polarity)
- Automatic switch off after approximately 15 minutes
- Removable test wires, user friendly
- Low energy consumption
- Removable test cables, easy to use
- Sold with a storage case
- AC Amps (0.1A - 1A): 400A / 600A
- DC amps (0.1A - 1A): 400A / 600A
- AC voltage (0.001V - 1V): 4V / 40V / 400V / 600V
- DC voltage (0.1mV - 1V): 400mV / 4V / 40V / 400V / 600V
- Hz frequency: 5Hz / 50Hz / 500Hz / 5kHz / 50kHz / 100kHz
- Resistance (0.1Ω - 0.01MΩ): 400Ω / 4kΩ / 40kΩ / 400kΩ / 4MΩ / 40MΩ
- Continuity test
- Diode test
- Low battery indicator
- LCD display: 3 1/2 digits, 1999 counts
- Sampling rate: 3 times per second
- Overload indicator: "OL" display and beep
- AAA 1.5V x 2 (included)



9DM2352

Weight (g)

402