



9TYN514



Hand and pneumatic hydraulic press (20, 30, 50 t)

- Safety valve.
- Pneumatic and manual double speed pump.
- Protective cover.
- Pneumatic foot pedal.
- Swivel handle and handle support for winch.
- Ergonomics Handle & Handle holder.
- Winch protection cover and pulley protection cover for hand safety.
- Sliding cylinder with handle and positioning scale.
- Winch handle support.
- V block and 180° configuration.
- Handle support.
- Pulley protective cover.
- Dust cover.
- Screw extension.
- Punch set.



|  | Capacity (ton) | A (mm) | D (mm) | E (mm) | G1 (mm) | G2 (mm) | R2 (mm) | R1 (mm) | R (mm) | M (mm) | Air Pressure (bar) | Width L3 (mm) | Height H5 (mm) | Supply pressure (bar) | Width between feet L12 (mm) | Weight (kg) |
|------------------------------------------------------------------------------------|----------------|--------|--------|--------|---------|---------|---------|---------|--------|--------|--------------------|---------------|----------------|-----------------------|-----------------------------|-------------|
| 9TYN51420AB | 20 | | 152 | 505 | 25 | 850 | 75 | 145 | 220 | 200 | 9 ~ 12 | 770 | 1800 | | 600 | 132 |



KING TONY

Enjoy your work

| | | | | | | | | | | | | | | |
|---------------------|----|-----|-----|-----|-----|----|-----|-----|-----|-----------|-----|------|-----|------------|
| 9TYN 5143 OAB | 30 | 200 | 535 | 130 | 830 | 75 | 145 | 220 | 280 | 9 ~ 12 | 930 | 1900 | 750 | 210 |
| 9TYN 5145 OAB | 50 | 200 | 535 | 80 | 780 | 75 | 145 | 220 | 280 | 9 ~ 12 | 930 | 1900 | 750 | 249.2 0 |