


906

## Copiglia

DIN 3129

- Sicurezza per i serraggi pneumatici
- Cromo Vanadio



	Lunghezza (mm)	ø D (mm)	Per applicazione di serie	Peso (g)
90608	14	2,5	3535M (6~12mm) 3435M (6~12mm) 3055M (4~12mm) 3065M (4~12mm) 3575M (E5~E14) 3535S (1/4"~1/2") 3435S (1/4"~1/2") 3055S (3/16"~1/2") 3053 (T10~T50) 3147, 3862, 3864	1
90609	16	2,5	3535M (13~19mm) 3435M (13~24mm) 3535S (9/16"~3/4") 3435S (9/16"~7/8") 3260, 3796	1
90601	20	3	4535M ( 8~14mm ) 4435M ( 8~14mm ) 4015M ( 5~14mm ) 4055M ( 4~14mm ) 4935M (10~14mm) 4415M ( 17mm) 4835M (10~17mm) 4530M ( 8~14mm ) 4535S ( 15/16"~9/16" ) 4435S ( 15/16"~9/16" ) 4015S ( 1/4"~1/2" ) 4055S ( 3/16"~1/2" ) 4935S ( 7/16"~9/16" ) 4575 ( E10~E18 )	2
90602	25	3	4535M ( 15~46mm ) 4435M ( 15~46mm )	2

			4015M ( 17.19mm ) 4415M ( 19.21mm ) 4530M ( 15~36mm ) 4575M ( E20 ) 4835M ( 19~30mm ) 4535S ( 11/16"~1-1/4" ) 4435S ( 5/8"~1-1/4" ) 4935M ( 16~30mm ) 4935S ( 11/16"~1-1/4" ) 4260, 4796, 4797, 4863, 4873, 4866	
90603	35	4	6535M (17~46mm) 6435M (19~46mm) 6935M (19~32mm) 6015M (21~27mm) 6530M (17~46mm) 6835M (17~32mm) 6535S (1-1/4" ~ 1-13/16" ) 6435S (1-1/16"~1-13/16" ) 6935S (1-1/16"~1-1/4" ) 609622M	2
90604	45	4	6535M ( 48~65mm ) 6435M ( 48~50mm ) 6535S ( 1-7/8" ~ 2-3/8" ) 6435S ( 1-7/8" ~ 2" )	2
90605	45	5	8535M ( 19~70mm ) 8435M ( 24~60mm ) 8835M ( 24~60mm ) 8535S ( 3/4"~2-3/4" ) 8435S ( 15/16"~2-1/4" ) 8514M, 8514S, 8534M, 806519M	3
90606	75	5	8535M (71~90mm) 8535S (2-13/16"~3-1/2")	4