

1422

Giravite con intaglio

DIN ISO 2380



- Lama tonda
- Lama in SNCM+V, impronta trattata
- Resistenza alle aggressioni chimiche e di prodotti petroliferi
- Impugnatura a doppio materiale PP+TPR
- Finizione cromata lucidata



|  | Larghezza impronta (mm) | Spessore impronta (mm) | Lunghezza Lama (mm) | Spessore lama (mm) | Peso (g) |
|---|-------------------------|------------------------|---------------------|--------------------|----------|
| 14226514R | 6.5 | 1.2 | 38 | 46 | 46 |
| 14220303R | 3.0 | 0.5 | 75 | 3.2 | 38 |
| 14220404R | 4.0 | 4.0 | 100 | 4 | 56 |
| 14220503R | 5.0 | 0.8 | 75 | 5 | 59 |
| 14220504R | 5.0 | 0.8 | 100 | 5 | 63 |
| 14225503R | 5.5 | 1.0 | 75 | 5 | 71 |
| 14225504R | 5.5 | 1.0 | 100 | 5 | 75 |
| 14225505R | 5.5 | 1.0 | 125 | 5 | 79 |
| 14225506R | 5.5 | 1.0 | 150 | 5 | 83 |
| 14226504R | 6.5 | 1.2 | 100 | 6 | 83 |
| 14226506R | 6.5 | 1.2 | 150 | 6 | 95 |
| 14220806R | 8.0 | 1.2 | 150 | 8 | 141 |
| 14220807R | 8.0 | 1.2 | 175 | 8 | 153 |



KING TONY

Enjoy your work

| | | | | | |
|-----------|------|-----|-----|----|-----|
| 14220808R | 8.0 | 1.2 | 200 | 8 | 163 |
| 14221008 | 10.0 | 1.6 | 200 | 10 | 214 |