

1060


M


Ringsteeksleutel metrisch

DIN 3113



- Metrisch
- 15° hellend oog
- Veelhoekige kop 12-kant
- Lage dikte
- Afwerking in gepolijst chroom



	Afmeting (mm)	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	L (mm)	Gewicht (g)
106055	5.5	15	11	4.3	4.3	105	16
106006	6	15.5	10.1	3.9	4.7	105	18
106007	7	17	11.5	4.1	5	115	20
106008	8	19.2	12.8	4.3	5.5	125	25
106009	9	21.2	14.2	4.5	5.9	135	34
106010	10	23.2	15.6	4.7	6.5	145	39
106011	11	25.3	16.9	5.1	6.9	155	46
106012	12	27.2	18.3	5.4	7.3	165	56
106013	13	29.4	19.7	5.6	7.8	175	69
106014	14	31.5	21.2	5.9	8.3	185	80
106015	15	33.2	22.5	6.1	8.6	195	93
106016	16	34.7	24	6.4	8.9	205	111
106017	17	36.5	25.3	6.6	9.3	215	119

106018	18	38.7	26.8	6.9	9.9	225	138
106019	19	40.7	28.1	7.1	10.5	235	158
106020	20	43.1	29.7	7.4	10.9	245	182
106021	21	44.8	31.3	7.7	11.3	255	203
106022	22	46.9	32.6	7.9	11.5	265	225
106023	23	48.3	34.2	8.1	11.8	275	251
106024	24	50.4	35.5	8.4	12.1	285	287
106025	25	52	36.9	8.6	12.5	295	326
106026	26	53.6	38.2	8.9	12.8	305	344
106027	27	55.7	39.6	9.1	13.1	315	371
106028	28	57.6	40.9	9.4	13.3	325	387
106029	29	59.7	42.3	9.6	13.5	335	456
106030	30	61.8	43.7	9.8	13.7	345	514
106032	32	65.8	46.4	10.1	14.3	365	557