

1432


Preciesleufkopschroevendraaier

DIN 5263



- Rond mes
- Lemmet in SNCM+V, behandelde punt
- PP handgreep (polypropyleen)
- Rotatiegedeelte aan het uiteinde van de schroevendraaier
- Afwerking in gesatineerd chroom



	Tip breedte (mm)	Tip dikte (mm)	Mes lengte (mm)	ø (mm)	Gewicht (g)
14320615	0.6	0.15	40	3.0	9
14320815	0.8	0.19	40	3.0	9
14321015	1.0	0.20	40	3.0	10
14321515	1.5	0.23	40	3.0	9
14321815	1.8	0.30	40	3.0	9
14322015	2.0	0.40	40	2.0	7
14322515	2.5	0.40	40	2.5	11
14323015	3.0	0.50	40	3.0	13
14323515	3.5	0.60	40	3.5	14
14324015	4.0	0.80	40	4.0	15
14321003	1.0	0.20	75	3.0	12
14321503	1.5	0.23	75	3.0	11
14321803	1.8	0.30	v	3.0	12

14322003	2.0	0.40	75	2.0	13
14322503	2.5	0.40	75	2.5	13
14323003	3.0	0.50	75	3.0	14
14323503	3.5	0.60	75	v	17
14324003	4.0	0.80	75	4.0	19