

SQ22

Standaardboor



- HSS-R gelamineerd staal
- Voor zacht staal, gelegeerd en laag-gelegeerd (weerstand 900 N/mm²), gietijzer, aluminium, lage legering, kunststoffen en hout

	Afmeting (mm)	Schroeflengte (mm)	Lengte (mm)	Gewicht (g)
SQ2201	1	12	34	3
SQ2215	1.5	18	40	3
SQ2202	2	24	49	4
SQ2225	2.5	30	57	4
SQ2203	3	33	61	5
SQ2235	3.5	39	70	5
SQ2204	4	43	75	6
SQ2245	4.5	4.5	47	80
SQ2205	5	52	86	11
SQ2255	5.5	57	93	14
SQ2206	6	57	93	15
SQ2265	6.5	63	101	19
SQ2207	7	69	109	23
SQ2275	7.5	69	109	26
SQ2208	8	75	117	30
SQ2285	8.5	75	117	33
SQ2209	9	81	125	41
SQ2295	9.5	81	125	47
SQ22100	10	87	133	51
SQ22105	10.5	87	133	51

SQ22110	11	94	142	65
SQ22115	11.5	94	142	69
SQ22120	12	101	151	78
SQ22125	12.5	101	151	86
SQ22130	13	101	151	89