


904



### Anel

- Segurança para aperto pneumático
- Anel de borracha

	Comprimento (mm)	ø D (mm)	Aplicado a tamanhos de suporte	Peso (g)
90401	19	3,5	4535M ( 8~14mm ) 4435M ( 8~14mm ) 4015M ( 5~14mm ) 4055M ( 4~14mm ) 4935M (10~14mm) 4415M ( 17mm) 4835M (10~17mm) 4530M ( 8~14mm ) 4535S ( 15/16"~9/16" ) 4435S ( 15/16"~9/16" ) 4015S ( 1/4"~1/2" ) 4055S ( 3/16"~1/2" ) 4935S ( 7/16"~9/16" ) 4575 ( E10~E18 )	2
90402	23	3,5	4535M ( 15~46mm ) 4435M ( 15~46mm ) 4015M ( 17.19mm ) 4415M ( 19.21mm ) 4530M ( 15~36mm ) 4575M ( E20 ) 4835M ( 19~30mm ) 4535S ( 11/16"~1-1/4" ) 4435S ( 5/8"~1-1/4" ) 4935M ( 16~30mm ) 4935S ( 11/16"~1-1/4" ) 4260, 4796, 4797, 4863, 4873, 4866	2
90403	33	3,5	6015M ( 14~19mm ) 6510M ( 17~30mm ) 6515M ( 17~30mm ) 6435S ( 3/4"~1" ) 6535S (	2

			11/16"~1-3/16" ) 6935S ( 3/4"~1" ) 609616M, 609622M	
90404	37	5,5	6535M (17~46mm) 6435M (19~46mm) 6935M (19~32mm) 6015M (21~27mm) 6530M (17~46mm) 6835M (17~32mm) 6535S (1-1/4" ~ 1-13/16" ) 6435S (1-1/16"~1-13/16") 6935S (1-1/16"~1-1/4") 609622M	2
90405	44	5,5	6535M ( 48~65mm ) 6435M ( 48~50mm ) 6535S ( 1-7/8" ~ 2-3/8" ) 6435S ( 1-7/8" ~ 2" )	2
90406	75	10	8535M ( 71~90mm ) 8535S ( 2-13/16"~3-1/2" )	4