



6535S

S 3/4" Standard 6 points impact socket

ANSI / ASME B107.2

- Polegada
- Cromo molibdênio
- Acabamento em fosfato



|  | Dimensões (polegadas) | D1 (mm) | D2 (mm) | L (mm) | l (mm) | Peso (g) |
|--|-----------------------|---------|---------|--------|--------|----------|
| 653522S | 11/16" | 29 | 38 | 50 | 10 | 225 |
| 653524S | 3/4" | 32 | 38 | 50 | 10 | 238 |
| 653526S | 13/16" | 35 | 38 | 50 | 13 | 252 |
| 653528S | 7/8" | 36 | 38 | 50 | 13 | 257 |
| 653530S | 15/16" | 37 | 38 | 50 | 15 | 288 |
| 653532S | 1" | 38 | 38 | 53 | 15 | 320 |
| 653534S | 1-1/16" | 42 | 40 | 53 | 18 | 325 |
| 653536S | 1-1/8" | 45 | 40 | 53 | 18 | 355 |
| 653538S | 1-3/16" | 46 | 40 | 53 | 20 | 365 |
| 653540S | 1-1/4" | 48 | 44 | 57 | 20 | 460 |
| 653542S | 1-5/16" | 50 | 44 | 57 | 20 | 479 |
| 653544S | 1-3/8" | 52 | 44 | 57 | 22 | 497 |
| 653546S | 1-7/16" | 54 | 44 | 57 | 22 | 529 |

| | | | | | | |
|---------|----------|----|----|----|----|------|
| 653548S | 1-1/2" | 56 | 44 | 57 | 22 | 540 |
| 653550S | 1-9/16" | 58 | 44 | 58 | 22 | 567 |
| 653552S | 1-5/8" | 59 | 44 | 58 | 24 | 580 |
| 653554S | 1-11/16" | 62 | 44 | 58 | 24 | 636 |
| 653556S | 1-3/4" | 64 | 44 | 62 | 24 | 676 |
| 653558S | 1-13/16" | 66 | 44 | 62 | 24 | 717 |
| 653560S | 1-7/8" | 68 | 54 | 65 | 26 | 925 |
| 653562S | 1-15/16" | 70 | 54 | 65 | 26 | 955 |
| 653566S | 2-1/16" | 74 | 54 | 68 | 30 | 1078 |
| 653568S | 2-1/8" | 76 | 54 | 68 | 30 | 1122 |
| 653570S | 2-3/16" | 77 | 54 | 70 | 30 | 1151 |
| 653572S | 2-1/4" | 79 | 54 | 70 | 32 | 1208 |
| 653574S | 2-5/16" | 81 | 54 | 70 | 32 | 1245 |
| 653576S | 2-3/8" | 84 | 54 | 70 | 32 | 1349 |